



3.0m/10ft Standard Performance Dual Polarized Microwave Parabolic Antenna

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Famous
- Certification: CE ISO9001
- Model Number: XPD Antenna
- Minimum Order Quantity: 1 SET
- Price: Negotiable
- Packaging Details: Standard export packaging/customizable packaging
- Payment Terms: T/T L/C



Product Specification

- Diameter Of Mounting Pole: $\phi 114$ Mm
- Fine Azimuth Adjustment: Coarse 360° Fine $\pm 5^\circ$
- Fine Elevation Adjustment: Fine $\pm 5^\circ$
- Wind Velocity Operational: 180km/h
- Wind Velocity Survival: 200km/h
- Ice-load: 25.4 Mm
- Operational Temperature: $-55 \sim +70$
- Highlight: **3m Dual Parabolic Antenna,
Microwave Dual Parabolic Antenna,
10ft Microwave Parabolic Antenna**

for more products please visit us on mw-antenna.com

Product Description

3.0m/10ft standard performance dual-polarized microwave parabolic antenna

- Our patent split-lobe microwave communication parabolic antenna for large diameter, which can save packaging and transportation costs greatly without any quality compromised
- High performance ultra high XPD parabolic antennas – Excellent performance for a wide range of applications
- Simple Assembly – Minimal required assembly simplifies installation on site and guarantees "factory-tested" quality

Electrical performance:

Antenna Model	Antenna Size(m/ft)	Frequency (GHZ)	Gain(dBi)			3dB BW (degs)	XPD (dB)	VSWR	F/B radio dB)	ISO
			Low	Mid	Top					
CMP303DA	3.0m/10ft	3.6-4.2	38.3	38.9	39.5	1.9	30	1.15	64	35
CMP304DA	3.0m/10ft	4.4-5.0	40	40.6	41.1	1.5	30	1.15	65	35
CMP306WDA	3.0m/10f	5.925-7.125	42.8	43.6	44.4	1.1	30	1.1	69	35
CMP307WDA	3.0m/10ft	7.125-8.5	44.4	45.2	46.0	0.9	30	1.1	71	35
CMP3010WDA	3.0m/10ft	10-11.7	47.4	48.1	48.7	0.7	30	1.1	73	35
CMP3013WDA	3.0m/10ft	12.2-13.25	49.4	49.6	49.8	0.6	30	1.1	75	35

Mechanical performance:

Diameter of Mounting Pole	Φ114 mm
Fine Azimuth Adjustment	Coarse 360° Fine ±5°
Fine Elevation Adjustment	Fine ±5°
Wind Velocity Operational	180km/h
Wind Velocity Survival	200km/h
Ice-load	25.4 mm
Operational Temperature	-55~ +70

- 1.The low/mid/high gain has≤-0.5dBi tolerance is within the normal range;
- 2.F/Bradio:Denotes highest radiation relative to the main beam,at 180°±40°,across the band.Production antennas do not exceed rated values by more than 2 dB unless stated otherwise;



Wuxi Famous Communication Equipment Co., Ltd.

+86 13255118228

eric@mw-antenna.com

mw-antenna.com

Room 803, Wisdom Building, No. 18 Wisdom Road, Huishan Economic Development Zone, Huishan District, Wuxi City, Jiangsu Province, China