# **Wuxi Famous Communication Equipment Co., Ltd**

# **Ultra High XPD Microwave Parabolic Antenna For Large Diameter And Excellent Performance**

## **Basic Information**

. Place of Origin: China . Brand Name: Famous **CE ISO9001** · Certification: Model Number: XPD Antenna • Minimum Order Quantity: 1 SET • Price: Negotiable

Standard export packaging/customizable Packaging Details:

packaging

• Payment Terms: T/T L/C



# **Product Specification**

• Diameter Of Mounting Pole: φ114 Mm

• Fine Azimuth Adjustment: Coarse 360°Fine±5°

• Fine Elevation Adjustment: Fine±5° • Wind Velocity Operational: 180km/h • Wind Velocity Survival: 200km/h • Ice-load: 25.4 Mm • Operational Temperature: -55~+70

. Highlight: **Excellent Performance XPD Antenna**,

Large Diameter XPD Antenna, **XPD Microwave Parabolic Antenna** 

## **Product Description**

#### 3.0m/10ft high XPD performance dual-polarized microwave parabolic antenna specification

The XPD Antenna is an innovative solution that addresses the challenges of interference and signal degradation in wireless communication systems, making it an essential component for achieving high-quality, reliable, and high-speed data transmission.

#### **Electrical performance:**

|               | Antenne<br>Size(m/ft) | Frequency   | Gain(dBi) |      |      |                  |             |      |                   |     |
|---------------|-----------------------|-------------|-----------|------|------|------------------|-------------|------|-------------------|-----|
| Antenna Model |                       |             | LoW       | Mid  | Тор  | 3dB BW<br>(degs) | XPD<br>(dB) | VSWR | F/B radio<br>(dB) | ISO |
| CMP303DB      | 3.0m/10ft             | 3.6-4.2     | 38.3      | 38.9 | 39.5 | 1.9              | 33          | 1.15 | 64                | 38  |
| CMP304DB      | 3.0m/10ft             | 4.4-5.0     | 40        | 40.6 | 41.1 | 1.5              | 33          | 1.15 | 65                | 38  |
| CMP306WDB     | 3.0m/10ft             | 5.925-7.125 | 42.8      | 43.6 | 44.4 | 1.1              | 33          | 1.1  | 69                | 38  |
| CMP307WDB     | 3.0m/10ft             | 7.125-8.5   | 44.4      | 45.2 | 46.0 | 0.9              | 33          | 1.1  | 71                | 38  |
| CMP3010WDB    | 3.0m/10ft             | 10-11.7     | 47.4      | 48.1 | 48.7 | 0.7              | 33          | 1.1  | 73                | 38  |
| CMP3013WDB    | 3.0m/10f              | 12.2-13.25  | 49.4      | 49.6 | 49.8 | 0.6              | 33          | 1.1  | 75                | 38  |

#### Mechanical performance:

| Diameter of Mounting Pole | Ф114 mm              |  |  |  |  |
|---------------------------|----------------------|--|--|--|--|
| Fine Azimuth Adjustment   | Coarse 360° Fine ±5° |  |  |  |  |
| Fine Elevation Adjustment | Fine ±5°             |  |  |  |  |
| Wind Velocity Operational | 180km/h              |  |  |  |  |
| Wind Velocity Survival    | 200km/h              |  |  |  |  |
| lce-load                  | 25.4 mm              |  |  |  |  |
| Operational Temperature   | -55~ +70             |  |  |  |  |

- 1. The low/mid/high gain has≤-0.5dBi tolerance is within the normal range;
- 2.F/Bradio:Denotes highest radiation relative to the main beam,at 180°±40°, across the band. Production antennas do not exceed rated values by more than 2 dB unless stated otherwise;



**Wuxi Famous Communication Equipment Co., Ltd.** 



+86 13255118228



eric@mw-antenna.com



mw-antenna.com